

## PM500 Pressure Measurement Modules



### Wichtigste Merkmale

For [2271A Industrial Pressure Calibrator](#) and 6270A, 8270A and 8370A Pressure Controller / Calibrators

### Produktübersicht: PM500 Pressure Measurement Modules

#### Key features:

- Highly characterized and linearized silicon pressure sensor provides an economical way of making accurate pressure measurements
- 0.01% of reading measurement uncertainty from 50% to 100% for most ranges allows for wide workload coverage
- More than 45 ranges, from low differential pressures up to 20 MPa (3000 psi) to choose from. Your application is covered with this wide flexibility in configuration.

### Technische Daten: PM500 Pressure Measurement Modules

## Performance specifications

The performance specifications describe the complete instrumental uncertainty of the Product. The specifications include all relevant error components (linearity, hysteresis, repeatability, resolution, reference standard measurement uncertainty, 1-year drift, and temperature effects). The specifications are provided at a level of confidence of 95 %, k=2, normally distributed. Precision uncertainty includes linearity, hysteresis, repeatability, resolution, and temperature effects.

## PM500 Modules measurement specifications

Specifications are valid from 15 °C to 35 °C.

Model	Range (SI Units)	Range (Imperial Units)	Measurement Mode <sup>2</sup>	1-Year Instrumental Uncertainty <sup>7</sup>	1-Year Zero Instrumental Drift % FS, RSS with 1-Year Instrumental Uncertainty <sup>1</sup>	Precision Uncertainty <sup>8</sup>
PM500-G100K <sup>4</sup>	0 kPa to 100 kPa	0 psi to 15 psi	gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-G200K <sup>4</sup>	0 kPa to 200 kPa	0 psi to 30 psi	gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-G250K <sup>4</sup>	0 kPa to 250 kPa	0 psi to 36 psi	gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-G350K <sup>4</sup>	0 kPa to 350 kPa	0 psi to 50 psi	gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-G400K <sup>4</sup>	0 kPa to 400 kPa	0 psi to 60 psi	gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-G600K <sup>4</sup>	0 kPa to 600 kPa	0 psi to 90 psi	gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-G700K <sup>5</sup>	0 kPa to 700 kPa	0 psi to 100 psi	gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG1M <sup>5</sup>	-0.1 MPa to 1 MPa	-15 psi to 150 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG1.4M <sup>5</sup>	-0.1 MPa to 1.4 MPa	-15 psi to 200 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG2M <sup>5</sup>	-0.1 MPa to 2 MPa	-15 psi to 300 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG2.5M <sup>5</sup>	-0.1 MPa to 2.5 MPa	-15 psi to 400 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG3.5M <sup>5</sup>	-0.1 MPa to 3.5 MPa	-15 psi to 500 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG4M <sup>5</sup>	-0.1 MPa to 4 MPa	-15 psi to 600 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035

PM500-BG7M <sup>5</sup>	-0.1 MPa to 7 MPa	-15 psi to 1000 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG10M <sup>5</sup>	-0.1 MPa to 10 MPa	-15 psi to 1500 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG14M <sup>5</sup>	-0.1 MPa to 14 MPa	-15 psi to 2000 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BG20M <sup>5</sup>	-0.1 MPa to 20 MPa	-15 psi to 3000 psi	bi-directional gauge	0.01 or 0.005	-	0.007 or 0.0035
PM500-BA120K <sup>3,6</sup>	60 kPa to 120 kPa	8 psi to 17 psi	absolute	0.01 % of reading	0.05	0.005 % of reading
PM500-A120K <sup>3,6</sup>	0.08 kPa to 120 kPa	0.01 psi to 16 psi	absolute	0.01 or 0.005	0.05	0.007 or 0.0035
PM500-A160K <sup>3,6</sup>	0.08 kPa to 160 kPa	0.01 psi to 23 psi	absolute	0.01 or 0.005	0.05	0.007 or 0.0035
PM500-A200K <sup>3,4</sup>	0.08 kPa to 200 kPa	0.01 psi to 30 psi	absolute	0.01 or 0.005	0.05	0.007 or 0.0035
PM500- A350K <sup>4</sup>	0.08 kPa to 350 kPa	0.01 psi to 50 psi	absolute	0.01 or 0.005	0.03	0.007 or 0.0035
PM500- A700K <sup>4</sup>	0.08 kPa to 700 kPa	0.01 psi to 100 psi	absolute	0.01 or 0.005	0.025	0.007 or 0.0035
PM500- A1.4M <sup>5</sup>	0.035 MPa to 1.4 MPa	5 psi to 200 psi	absolute	0.01 or 0.005	0.015	0.007 or 0.0035
PM500-A2M <sup>5</sup>	0.07 MPa to 2 MPa	10 psi to 300 psi	absolute	0.01 or 0.005	0.015	0.007 or 0.0035
				(% FS + % of reading)		(% FS + % of reading)
PM500- G2.5K <sup>6</sup>	0 kPa to 2.5 kPa	0 inH <sub>2</sub> O to 10 inH <sub>2</sub> O	gauge	0.03 + 0.02	-	0.015 + 0.01
PM500-G7K <sup>6</sup>	0 kPa to 7 kPa	0 inH <sub>2</sub> O to 30 inH <sub>2</sub> O	gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-G14K <sup>6</sup>	0 kPa to 14 kPa	0 inH <sub>2</sub> O to 50 inH <sub>2</sub> O	gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-G20K <sup>6</sup>	0 kPa to 20 kPa	0 inH <sub>2</sub> O to 80 inH <sub>2</sub> O	gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-G35K <sup>6</sup>	0 kPa to 35 kPa	0 psi to 5 psi	gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-G70K <sup>6</sup>	0 kPa to 70 kPa	0 psi to 10 psi	gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-NG100K <sup>6</sup>	-100 kPa to 0 kPa	-15 psi to 0 psi	negative gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-BG1.4K <sup>6</sup>	-1.4 kPa to 1.4 kPa	-5 inH <sub>2</sub> O to 5 inH <sub>2</sub> O	bi-directional gauge	0.03 + 0.02	-	0.015 + 0.01
PM500-BG2.5K <sup>6</sup>	-2.5 kPa to 2.5 kPa	-10 inH <sub>2</sub> O to 10 inH <sub>2</sub> O	bi-directional gauge	0.03 + 0.02	-	0.015 + 0.01

PM500-BG3.5K <sup>6</sup>	-3.5 kPa to 3.5 kPa	-15 inH <sub>2</sub> O to 15 inH <sub>2</sub> O	bi-directional gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-BG7K <sup>6</sup>	-7 kPa to 7 kPa	-30 inH <sub>2</sub> O to 30 inH <sub>2</sub> O	bi-directional gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-BG14K <sup>6</sup>	-14 kPa to 14 kPa	-50 inH <sub>2</sub> O to 50 inH <sub>2</sub> O	bi-directional gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-BG25K <sup>6</sup>	-25 kPa to 25 kPa	-100 inH <sub>2</sub> O to 100 inH <sub>2</sub> O	bi-directional gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-BG40K <sup>6</sup>	-40 kPa to 40 kPa	-6 psi to 6 psi	bi-directional gauge	0.01 + 0.01	-	0.005 + 0.005
PM500-BG60K <sup>6</sup>	-60 kPa to 60 kPa	-9 psi to 9 psi	bi-directional gauge	0.01 + 0.01	-	0.005 + 0.005
				% FS		% FS
PM500-BG100K <sup>4</sup>	-100 kPa to 100 kPa	-15 psi to 15 psi	bi-directional gauge	0.01	-	0.005
PM500-BG200K <sup>4</sup>	-100 kPa to 200 kPa	-15 psi to 30 psi	bi-directional gauge	0.01	-	0.005
PM500-BG250K <sup>4</sup>	-100 kPa to 250 kPa	-15 psi to 36 psi	bi-directional gauge	0.01	-	0.005
PM500-BG350K <sup>4</sup>	-100 kPa to 350 kPa	-15 psi to 50 psi	bi-directional gauge	0.01	-	0.005
PM500-BG400K <sup>4</sup>	-100 kPa to 400 kPa	-15 psi to 60 psi	bi-directional gauge	0.01	-	0.005
PM500-BG700K <sup>5</sup>	-100 kPa to 700 kPa	-15 psi to 100 psi	bi-directional gauge	0.01	-	0.005

Notes

1. The 1 Year Instrumental Uncertainty is specified with a zeroing technique in the Operators Manual. If not adhered to the 1 Year Instrumental Uncertainty is:
2. PM500 gauge or bi-directional mode modules support absolute mode measurement when used with a Barometric Reference Module. Instrumental uncertainty for gauge mode modules used in absolute mode by addition of a barometric reference module is calculated as the uncertainty of the gauge mode module root sum squared with the uncertainty of the barometric reference module. Uncertainty for gauge mode assumes routine zeroing which is default operation mode when used in a chassis.
3. These modules can be used as barometric reference modules on all chassis.
4. Compatible with 2271A, 6270A and 8270A
5. Compatible with 2271A, 6270A, 8270A and 8370A
6. Compatible with 2271A and 6270A
7. (% of reading or % FS, whichever is greater) unless otherwise stated
8. (% of reading or % FS, whichever is greater)

## Modelle



### **PM500-G20K**

Pressure measurement module 0 to 20 kPa (0 to 80 inh2o) gauge

---

### **PM500-G35K**

Pressure measurement module 0 to 35 kPa (0 to 5 psi) gauge

---

### **PM500-G70K**

Pressure measurement module 0 to 70 kPa (0 to 10 psi) gauge

---

### **PM500-G100K**

Pressure measurement module 0 to 100 kPa (0 to 15 psi) gauge

---

### **PM500-G200K**

Pressure measurement module 0 to 200 kPa (0 to 30 psi) gauge

---

### **PM500-G250K**

Pressure measurement module 0 to 250 kPa (0 to 36 psi) gauge

---

### **PM500-G350K**

Pressure measurement module 0 to 350 kPa (0 to 50 psi) gauge

---

### **PM500-G400K**

Pressure measurement module 0 to 400 kPa (0 to 60 psi) gauge

---

**PM500-G600K**

Pressure measurement module 0 to 600 kPa (0 to 90 psi) gauge

---

**PM500-G700K**

Pressure measurement module 0 to 700 kPa (0 to 100 psi) gauge

---

**PM500-BG3.5K**

Pressure measurement module -3.5 to 3.5 kPa (-15 to 15 inh<sub>2</sub>o) gauge

---

**PM500-BG7K**

Pressure measurement module -7 to 7 kPa (-30 to 30 inh<sub>2</sub>o) gauge

---

**PM500-BG14K**

Pressure measurement module -14 to 14 kPa (-50 to 50 inh<sub>2</sub>o) gauge

---

**PM500-BG25K**

Pressure measurement module -25 to 25 kPa (-100 to 100 inh<sub>2</sub>o) gauge

---

**PM500-BG40K**

Pressure measurement module -40 to 40 kPa (-6 to 6 psi) gauge

---

**PM500-BG60K**

Pressure measurement module -60 to 60 kPa (-9 to 9 psi) gauge

---

**PM500-BG100K**

Pressure measurement module -100 to 100 kPa (-15 to 15 psi) gauge

---

**PM500-BG200K**

Pressure measurement module -100 to 200 kPa (-15 to 30 psi) gauge

---

**PM500-BG250K**

Pressure measurement module -100 to 250 kPa (-15 to 36 psi) gauge

---

**PM500-BG350K**

Pressure measurement module -100 to 350 kPa (-15 to 50 psi) gauge

---

**PM500-BG400K**

Pressure measurement module -100 to 400 kPa (-15 to 60 psi) gauge

---

**PM500-BG700K**

Pressure measurement module -100 to 700 kPa (-15 to 100 psi) gauge

---

**PM500-BG1M**

Pressure measurement module -0.1 to 1 mpa (-15 to 150 psi) gauge

---

**PM500-BG1.4M**

Pressure measurement module -0.1 to 1.4 mpa (-15 to 200 psi) gauge

---

**PM500-BG2M**

Pressure measurement module -0.1 to 2 mpa (-15 to 300 psi) gauge

---

**PM500-BG2.5M**

Pressure measurement module -0.1 to 2.5 mpa (-15 to 400 psi) gauge

---

**PM500-BG3.5M**

Pressure measurement module -0.1 to 3.5 mpa (-15 to 500 psi) gauge

---

**PM500-BG4M**

Pressure measurement module -0.1 to 4 mpa (-15 to 600 psi) gauge

---

**PM500-BG7M**

Pressure measurement module -0.1 to 7 mpa (-15 to 1000 psi) gauge

---

**PM500-BG10M**

Pressure measurement module -0.1 to 10 mpa (-15 to 1500 psi) gauge

---

**PM500-BG14M**

Pressure measurement module -0.1 to 14 mpa (-15 to 2000 psi) gauge

---

**PM500-BG20M**

Pressure measurement module -0.1 to 20 mpa (-15 to 3000 psi) gauge

---

**PM500-A120K**

Pressure measurement module 120 kPa (16 psi) absolute

---

**PM500-A160K**

Pressure measurement module 160 kPa (23 psi) absolute

---

**PM500-A200K**

Pressure measurement module 200 kPa (30 psi) absolute

---

**PM500-A350K**

Pressure measurement module 350 kPa (50 psi) absolute

---

**PM500-A700K**

Pressure measurement module 700 kPa (100 psi) absolute

---

**PM500-A1.4M**

Pressure measurement module 1.4 mpa (200 psi) absolute

---

**PM500-A2M**

Pressure measurement module 2 mpa (300 psi) absolute

---



**Fluke.** *Damit Ihre Welt intakt bleibt.*

**Fluke (Switzerland) GmbH**

Industrial Division  
Hardstrasse 20  
CH-8303 Bassersdorf  
Telefon: +41 (0) 44 580 7504  
E-Mail: [info@ch.fluke.nl](mailto:info@ch.fluke.nl)  
[www.fluke.ch](http://www.fluke.ch)

©2025 Fluke Corporation. Alle Rechte vorbehalten.  
Anderungen vorbehalten  
04/2025

**Technischer Beratung:**

Beratung zu Produkteigenschaften, Spezifikationen,  
Messgeräte und Anwendungsfragen  
Tel.: +49 (0) 7684 8 00 95 45  
E-Mail: [techsupport.dach@fluke.com](mailto:techsupport.dach@fluke.com)

**Dieses Dokument darf nicht ohne die schriftliche  
Genehmigung der Fluke Corporation geändert  
werden.**