

Datos técnicos

7040 Refrigerated Temperature Calibration Bath



Descripción general del producto: 7040 Refrigerated Temperature Calibration Bath

This bath operates at temperatures as low as -40 °C, and is built using CFC-free refrigerants. Fluke Calibration's proprietary controller design and unique tank construction produce bath stabilities to ± 0.001 °C or better. These baths are so stable and uniform that national labs use them for comparison calibrations and fixed-point cell maintenance.

The bath is fully automatable with a bath interface package and Fluke Calibration's MET/TEMP II automation software package. When we automate a bath, we automate it completely with computer-controlled solenoid valves for precision balancing of the heating and cooling system. MET/TEMP II performs all calibration tasks automatically, using your PC.

With a Fluke Calibration cold bath, you can forget external coolants. Internal refrigeration systems are all that's needed to reach each bath's coldest temperature. Most cold baths may be ordered with an optional pumping lid for supplying external cooling requirements.

Especificaciones: 7040 Refrigerated Temperature Calibration Bath

Specifications	
Model	7040
Range	-40 °C to 110 °C
Stability	±0.002 °C at -40 °C (ethanol) ±0.0015 °C at 25 °C (water) ±0.003 °C at 100 °C (oil 5012)
Uniformity	±0.004 °C at -40 °C (ethanol) ±0.002 °C at 25 °C (water) ±0.004 °C at 100 °C (oil 5012)
Temperature Seing	Digital display with push-button data entry
Set-Point Resolution	0.01 °C; high-resolution mode, 0.00007 °C
Display Resolution	0.01 °C
Digital Seing Accuracy	±1 °C
Digital Seing Repeatability	±0.01 °C
Heaters	500 and 1000 W
Access Opening (call for customs)	127 x 254 mm(5 x 10 in)
Depth	305 mm (12 in)
Weld Parts	304 Stainless Steel
Power	115 VAC (±10 %), 60 Hz, 16 A or 230 VAC (±10 %), 50 or 60 Hz, 9 A (specify voltage and frequency)
Volume	27 liters (7.2 gal)
Weight	63.5 kg (40 lb)
Size	622 x 768 x 483 mm (24.5 x 30.25 x 19 in)
Automation	Use the 1586A Super-DAQ to automate temperature sensor calibration

Modelos



7040

Baño estándar, de -40 °C a 110 °C

2033

Cono IR (diseño NIST)

The Fluke logo is located in the top right corner of the page. It consists of the word "FLUKE" in a bold, black, sans-serif font, with a registered trademark symbol (®) at the end.

Fluke. Manteniendo su mundo en marcha.

Fluke Corporation
Everett, WA 98206 EE.UU.

Para obtener información adicional En EE. UU.
(800) 443-5853
En Europa/Medio Oriente/África
+31 (0)40 267 5100
En Canadá (800)-36-FLUKE
www.fluke.com

Latin America
Tel: +1 (425) 446-5500
www.fluke.com/es-bo

©2025 Fluke Corporation. Reservados todos los derechos. Impreso en los Países Bajos. Información sujeta a modificación sin previo aviso.
04/2025

No está permitido modificar este documento sin autorización por escrito de Fluke Corporation.