

Data teknis

3140-3 | Insert, 9140 "B" w/ cmprsn hls, ring



Ikhtisar Produk: 3140-3 | Insert, 9140 "B" w/ cmprsn hls, ring

Removable inserts are sized for probes with the named diameter. Use additional inserts to broaden the range of hole sizes available or to back up or replace existing inserts. This insert is designed for use with the 9140 Field Dry-Well.

- Insert "B" 9140
- Holes: ¼ in (2); 3/8 in (2); 3/16 in (2)

Spesifikasi: 3140-3 | Insert, 9140 "B" w/ cmprsn hls, ring

Hole size	Quantity
4.8 mm (3/16 in)	2
6.35 mm (1/4 in)	2
9.5 mm (3/8 in)	2

Model



3140-3

Insert, 9140 "B" w/ cmprsn hls, ring

Fluke. *Memastikan aktivitas Anda terus berjalan dan beroperasi.*

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:

In the U.S.A. (800) 443-5853

In Europe/M-East/Africa

+31 (0)40 267 5100

In Canada (800)-36-FLUKE

From other countries +1 (425) 446-5500

www.fluke.com

BUT. FLUKE SOUTH EAST ASIA PTE LTD

Menera Satu Sentra Kelapa Gading #06-05

Jl. Bulevar Kelapa Gading Kav. LA# No. 1

Summarecon Kelapa Gading

Jakarta Utara 14240

Indonesia

Tel: +62 21 2938 5922

Email: info.asean@fluke.com

www.fluke.com/id

©2025 Fluke Corporation. Specifications subject to change without notice.

04/2025

Modification of this document is not permitted without written permission from Fluke Corporation.