

Dados técnicos

Fluke BP880 BNC to Female Double Stacking Banana Plug



Características principais

- Allows for hands-free testing in controlled voltage environments 500 VRMS maximum
- Banana plug is nickel-plated, beryllium copper for low contact resistance
- The BNC shell is plated for tarnish resistance
- Operating temperature +50 °C (+122 °F) maximum

Descrição do produto: Fluke BP880 BNC to Female Double Stacking Banana Plug

Converts a BNC scope lead to a dual banana plug for connection to a DMM. Required when adapting a shielded BNC cable, found on high-end low current clamps such as the Fluke 80i-110s, to a DMM.

Modelos



Fluke BP880

BNC to Female Double Stacking Banana Plug

Fluke. *Keeping your world up and running.®*

Fluke Ibérica, S.L.
Pol. Ind. Valportillo
C/ Valgrande, 8
Ed. Thanworth II · Nave B1A
28108 Alcobendas
Madrid
Tel: +34 91 414 0100
E-mail: cs.es@fluke.com
www.fluke.pt
©2025 Fluke Corporation. Todos os direitos reservados.
Os dados fornecidos estão sujeitos a alterações sem aviso prévio.
04/2025

AresAgante, Lda.
Rua Caminho das Congostas, 320
4250-159 Porto
Tel: +351 2 2832 9400
E-mail: geral@aresagante.pt
www.aresagante.pt

A modificação deste documento não é permitida sem a autorização escrita da Fluke Corporation.