

ข้อมูลด้านเทคนิค

Fluke TPS VOLTPROBE 750 V



ภาพรวมผลิตภัณฑ์: Fluke TPS VOLTPROBE 750 V

Specifications

Range rms	4 V to 680 V
Vnom	400 V
Vmax. contin.	1000 V
Fast Transient Range $V_p < 1\text{ms}$	5 to 750 detects voltage harmonics > 50st with fast transient
Intrinsic error	0.2%
Operating voltage	600 V CAT IV

ข้อมูลจำเพาะ: Fluke TPS VOLTPROBE 750 V

Specifications	
Range rms	4 V to 680 V
Vnom	400 V
Vmax. contin.	1000 V
Fast Transient Range $V_p < 1\text{ ms}$	5 to 750 detects voltage harmonics > 50st with fast transient



insic error	0.2%
Operating voltage	600 V CAT IV

รุ่น



TPS VOLTPROBE 750V

Fluke TPS VOLTPROBE 750 V
VOLTPROBE 750 V

Fluke. ทั่วโลกของคุณ คงอยู่แค่ ปลายนิ้ว

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Europe/M-East/Africa
+31 (0)40 267 5100
In Canada (800)-36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com/th-th

©2025 Fluke Corporation. Specifications subject to
change without notice.
04/2025

Modification of this document is not permitted without
written permission from Fluke Corporation.