

技術資料

## Fluke 17B+ 數位萬用表





## 主要功能

- 600 V Cat III safety rating
- AC/DC voltage measurement up to 1000V
- AC/DC current measurement up to 10A
- Measures voltage, resistance, continuity, capacitance
- Frequency and temperature measurement
- Large easy-to-read display with bright white backlight

## 產品概述: Fluke 17B+ 數位萬用表

Fluke quality is always within your reach

Experience the precision, durability, and safety of a professional-grade test tool with the Fluke 17B+ Digital Multimeter. With the Fluke 17B+, you'll have a rugged, portable tool that's designed to be used with one hand, even while wearing gloves. It provides all the essential features you need in a digital multimeter, from AC/DC voltage and current measurements up to 1000V and 10A, to comprehensive capabilities including resistance, capacitance, and frequency checks. It also comes standard with a type K thermocouple so you can measure the temperature of things like your refrigeration systems, heat exchangers, and line sets. The 17B+ also supports relative measurements which allows you to zero out a source reading so you can easily measure changes in things like voltage drop or temperature making it ideal for identifying and diagnosing issues.

The CAT III 600V safety rating provides peace of mind for everything from routine checks on electrical equipment and appliances, to checking voltage levels at power outlets or switches, to diagnosing issues with circuits. If you're looking to build out your toolkit as a DIY enthusiast or early career electrician, look no further than the Fluke 17B+ Digital Multimeter, a reliable and versatile tool that provides the essential features you need.

## 規格: Fluke 17B+ 數位萬用表

### Accuracy Specifications

Accuracy is specified for 1 year after calibration, at operating temperatures of 18 °C to 28 °C, relative humidity at 0% to 75%. Accuracy specifications take the form of:  $\pm$ (% of Reading + Number of Least Significant Digits).

Function	Range	Resolution	Accuracy
AC volts (40 Hz to 500Hz) <sup>1</sup>	4.000 V 40.00 V 400.0 V 1000 V	0.001 V 0.01 V 0.1 V 1 V	1.0% + 3
DC volts	4.000 V 40.00 V 400.0 V 1000 V	0.001 V 0.01 V 0.1 V 1 V	0.5% + 3
AC millivolts	400.0 mV	0.1 mV	3.0% + 3
DC millivolts	400.0 mV	0.1 mV	1.0% + 10
Diode test <sup>2</sup>	2.000 V	0.001 V	10%
Resistance (Ohms)	400.0 Ω 4.000 kΩ 40.00 kΩ 400.0 kΩ 4.000 MΩ 40.00 MΩ	0.1 Ω 0.001 kΩ 0.01 kΩ 0.1 kΩ 0.001 MΩ 0.01 MΩ	0.5% + 3 0.5% + 2 0.5% + 2 0.5% + 2 0.5% + 2 1.5% + 3
Capacitance <sup>3</sup>	40.00 nF 400.0 nF 4.000 μF 40.00 μF 400.0 μF 1000 μF	0.01 nF 0.1 nF 0.001 μF 0.01 μF 0.1 μF 1 μF	2% + 5 2% + 5 5% + 5 5% + 5 5% + 5 5% + 5
Frequency <sup>1</sup> Hz (10 Hz – 100 kHz)	50.00 Hz 500.0 Hz 5.000 kHz 50.00 kHz 100.0 kHz	0.01 Hz 0.1 Hz 0.001 kHz 0.01 kHz 0.1 kHz	0.1% + 3
Duty Cycle <sup>1</sup>	1% to 99%	0.1%	1% typical <sup>4</sup>
AC current μA (40 Hz to 400 Hz)	400.0 μA 4000 μA	0.1 μA 1 μA	1.5% + 3
AC current mA (40 Hz to 400 Hz)	40.00 mA 400.0 mA	0.01 mA 0.1 mA	1.5% + 3
AC current A (40 Hz to 400 Hz)	4.000 A 10.00 A	0.001 A 0.01 A	1.5% + 3
DC current μA	400.0 μA 4000 μA	0.1 μA 1 μA	1.5% + 3
DC current mA	40.00 mA 400.0 mA	0.01 mA 0.1 mA	1.5% + 3
DC current A	4.000 A 10.00 A	0.001 A 0.01 A	1.5% + 3
Temperature	50 °C- 400 °C 0 °C- 50 °C -55 °C- 0 °C	0.1C	2% ±1 °C ±2 °C 9% ±2 °C
Backlight	-	-	Yes

<sup>1</sup>All ac, Hz, and duty cycle are specified from 1% to 100% of range. Inputs below 1% of range are not specified.

<sup>2</sup>Typically, open circuit test voltage is 2.0 V and short circuit current is <0.6 mA.

<sup>3</sup>Specifications do not include errors due to test lead capacitance and capacitance floor (may be up to 1.5 nF in the 40 nF range).

<sup>4</sup>Typical means when the frequency is at 50 Hz or 60 Hz and the duty cycle is between 10% and 90%.

Function	Overload protection	Input impedance (Nominal)	Common mode rejection ratio	Normal mode rejection ratio
AC volts	1000 V <sup>1</sup>	>10 MΩ <100 pF	>60 dB at dc, 50 Hz or 60 Hz	-
AC millivolts	400 mV	>1MΩ, <100 pF	>80 dB at 50 Hz or 60 Hz	-
DC volts	1000 V <sup>1</sup>	>10 MΩ <100 pF	>100 dB at dc, 50 Hz or 60 Hz	>60 dB at 50 Hz or 60 Hz
DC millivolts	400 mV	>1MΩ, <100 pF	>80 dB at 50 Hz or 60 Hz	-
<sup>1</sup> 10 <sup>6</sup> V Hz Max				
General specifications				
Maximum voltage between any terminal and earth ground		1000 V		
Display (LCD)		4000 counts, updates 3/sec		
Battery type		2 AA, NEDA 15A, IEC LR6		
Battery life		500 hours minimum		
Temperature				
Operating		0 °C to 40 °C		
Storage		-30 °C to 60 °C		
Relative humidity				
Operating humidity		Non-condensing (<10°C) ≤90% RH at 10 °C to 30 °C ≤75% RH at 30 °C to 40 °C		
		40 MΩ range ≤80% RH at 10 °C to 30 °C ≤70% RH at 30 °C to 40 °C		
Altitude				
Operating		2000 m		
Storage		12,000 m		
Temperature coefficient		0.1 X (specified accuracy) /°C (<18 °C or >28 °C)		
Fuse protection for current inputs		440 mA, 1000 V Fast Fuse, Fluke specified part only. 11A, 1000V Fast Fuse, Fluke specified part only.		
Size (H x W x L)		183 x 91 x 49.5 mm		
Weight		455 g		
IP rating		IP 40		
Safety		IEC 61010-1, IEC61010-2-030 CAT III 600 V, Pollution Degree 2		
Electromagnetic compatibility		IEC 61326-1: Portable EMC Environment		

Class A equipment (industrial broadcasting and communication equipment)<sup>1</sup>

<sup>1</sup> This product meets requirements for industrial (Class A) electromagnetic wave equipment and seller or user should take notice of it. This equipment is intended for use in business environments and is not to be used in homes.

Fluke. 保持您的世界運作不懈。

Fluke Corporation  
PO Box 9090, Everett, WA 98206 U.S.A.

更多資訊  
U.S.A. (800) 443-5853  
Europe/M-East/Africa  
+31 (0)40 267 5100  
Canada (800)-36-FLUKE  
其他 +1 (425) 446-5500  
[www.fluke.com/zh-tw](http://www.fluke.com/zh-tw)

©2025 Fluke Corporation. Specifications subject to  
change without notice.  
04/2025

Modification of this document is not permitted  
without written permission from Fluke Corporation.